

PUNCHES

PIN PUNCH



Reference	Point Diameter	Hex Stock	Length
AC-T5140-332	3/32"	1/4"	4 1/4"
AC-T5140-18	1/8"	3/8"	6"
AC-T5140-532	5/32"	3/8"	6"
AC-T5140-316A	3/16"	3/8"	6"
AC-T5140-732	7/32"	3/8"	6"
AC-T5140-316B	3/16"	1/2"	6"
AC-T5140-14	1/4"	1/2"	6"
AC-T5140-516	5/16"	1/2"	9"

CENTER PUNCH



Reference	Hex Stock	Length
AC-T5141-14	1/4"	4 1/2"
AC-T5141-38	3/8"	4 1/2"
AC-T5141-12	1/2"	6"
AC-T5141-58	5/8"	6 1/2"

OBLONG PUNCH



Reference	Inside Dimensions	
	Length	Width
AC-T5143-14	1/4"	5/64"
AC-T5143-38	3/8"	3/32"
AC-T5143-12	1/2"	7/64"
AC-T5143-58	5/8"	1/8"
AC-T5143-34	3/4"	9/64"
AC-T5143-78	7/8"	5/32"
AC-T5143-1	1"	5/32"
AC-T5143-1-18	1 1/8"	11/64"
AC-T5143-1-14	1 1/4"	11/64"
AC-T5143-1-38	1 3/8"	3/16"
AC-T5143-1-12	1 1/2"	13/64"
AC-T5143-1-58	1 5/8"	7/32"
AC-T5143-1-34	1 3/4"	7/32"
AC-T5143-1-78	1 7/8"	1/4"
AC-T5143-2	2"	1/4"

RIVET SETTERS



Reference	Copper Rivet No.
AC-T5142-1	#6
AC-T5142-2	#7
AC-T5142-3	#8
AC-T5142-4	#9
AC-T5142-5	#10, #11
AC-T5142-6	#12
AC-T5142-7	#13
AC-T5142-8	#14

PUNCHES

ARCH PUNCH

Arch punches are drop forged in one piece from the finest carbon steel. Larger sizes made with special 2 piece welded construction.

A unique feature of the Arch Punch is the inside taper which permits the punchings to clear easily through the barrel. Punches have fully polished barrel and black japanned handle. When ordering add diameter desired to end of order number.



Reference	Diameter	Reference	Diameter	Reference	Diameter
AC-T5144-316	3/16"	AC-T5144-1-116	1 1/16"	AC-T5144-2-38	2 3/8"
AC-T5144-14	1/4"	AC-T5144-1-18	1 1/8"	AC-T5144-2-12	2 1/2"
AC-T5144-516	5/16"	AC-T5144-1-316	1 3/16"	AC-T5144-2-58	2 5/8"
AC-T5144-38	3/8"	AC-T5144-1-14	1 1/4"	AC-T5144-2-34	2 3/4"
AC-T5144-716	7/16"	AC-T5144-1-516	1 5/16"	AC-T5144-2-78	2 7/8"
AC-T5144-12	1/2"	AC-T5144-138	1 3/8"	AC-T5144-3	3"
AC-T5144-916	9/16"	AC-T5144-1-716	1 7/16"	AC-T5144-3-18	3 1/8"
AC-T5144-58	5/8"	AC-T5144-1-12	1 1/2"	AC-T5144-3-14	3 1/4"
AC-T5144-1116	11/16"	AC-T5144-1-58	1 5/8"	AC-T5144-3-38	3 3/8"
AC-T5144-34	3/4"	AC-T5144-1-34	1 3/4"	AC-T5144-3-12	3 1/2"
AC-T5144-1316	13/16"	AC-T5144-1-78	1 7/8"	AC-T5144-3-58	3 5/8"
AC-T5144-78	7/8"	AC-T5144-2	2"	AC-T5144-3-34	3 3/4"
AC-T5144-1516	15/16"	AC-T5144-2-18	2 1/8"	AC-T5144-3-78	3 7/8"
AC-T5144-1	1"	AC-T5144-2-14	2 1/4"	AC-T5144-4	4"

RIVET KNOCKOUT AND ANVIL TOOL

May be used as an anvil or as a rivet knockout in the removal of rivet in shoes.

By removing the top section, a hole is exposed to permit quick and easy knockout of rivets. Milled slots allow convenient placement in vice.

Ref.: PEL-P-216001

